

啓昌紡織股份有限公司 Kiichang mesh

聚酯絲網技術參數表 Polyester mesh technical data

GP SCREEN FOR GRAPHIC PRINTING

網布目數 Mesh count	編織方式 Weave method	開孔寬度 Mesh opening	絲徑直徑 Thread diameter	開孔比率 Open surface	網布厚度 Mesh thickness	理論墨量 Theoretical ink volume
釐米 cm	pw	μm	μm	%	μm	cm ³ /m ²
32-100W	1:1	209	100	44.5	160	73.5
36-90W	1:1	183	90	43.3	150	64.9
36-100W	1:1	174	100	39.1	160	62.9
40-80W	1:1	170	80	45.0	130	46.8
43-80W	1:1	149	80	40.8	130	53.0
48-70W	1:1	133	70	41.0	110	45.1
61-55W	1:1	108	55	45.1	86	37.1
68-55W	1:1	85	55	33.5	86	28.4
77-55W	1:1	67	55	26.5	88	23.3
90-48W	1:1	55	48	24.6	81	19.9
90-48Y	1:1	55	48	24.6	81	19.9
100-40W	1:1	57	40	32.5	65	21.1
100-40Y	1:1	57	40	32.5	65	21.1
110-34W	1:1	54	34	35.2	54	19.3
110-34Y	1:1	54	34	35.2	54	19.3
120-31Y	1:1	49	31	35.0	49	17.2
120-34W	1:1	45	34	29.6	54	16.3
120-34Y	1:1	45	34	29.6	54	16.3
140-31W	1:1	36	31	26.0	48	12.5
140-31Y	1:1	36	31	26.0	48	12.5
140-34W	1:1	31	34	19.4	55	10.7
140-34Y	1:1	31	34	19.4	55	10.7
150-31Y	1:1	32	31	23.3	48	10.9
165-27Y	1:1	29	27	22.3	43	9.6
165-31Y	1:1	23	31	14.5	48	7.0